

## TECHNICAL DATA SHEET TWEHA WOODPROTECT

version number 3.3 dated July 1, 2018



EC number 32099000

**TWEHA WoodProtect provides excellent protection against wood rot in supporting framework of spruce (pine). TWEHA WoodProtect improves adhesion and resists moisture damage caused by water permeation, chemicals and acids where contacted by concrete, steel or brickwork.**

**Also for creating a black joint between façade panels.**

TWEHA WoodProtect has a closed cell structure which provides a perfect absorption for TWEHA Tape. TWEHA WoodProtect is not an adhesive-primer and may therefore never be used on the backside of façade panels.

The vertical frame construction or battens must be dry (wood moisture percentage < 18%, drying class 2 (NEN-EN 5461), air dried), dust- and grease free.

For the application of TWEHA WoodProtect use a paint tray with a clean, fine structure roller. Shake TWEHA WoodProtect thoroughly before use.

Apply TWEHA WoodProtect in one thin, full-cover layer (never more!).

Do not use TWEHA WoodProtect on painted wood, multiplex, aluminum or other types of metal.

TWEHA WoodProtect is not a primer and therefore can be pre-processed.

### Colour

- Black

### Packaging unit

- Can, 1 ltr.

### Work- and environmental safety

- Important information about working and environmental security is available through safety MSDS.

### Shelf life and storage conditions

- 18 months after production date
- Store in a cool, dry place

Parameter	Unit	Min. Value	Max. Value
Colour	black		
Density	Kg/l	0.9	1.1
Odour	Characteristic		
Drying time (20 °C)	hrs	2	



All specifications, recommendations and technical data are based on laboratory tests under optimum conditions resp. on practical experience. They have been compiled most carefully. Nevertheless, a claim cannot be derived from them. In view of the wide range and variability of substrates, we would advise that our product should be tested by the user to establish suitability for its intended application. The user bears the only responsibility for non-appropriate or other than specified applications.

We refer to our general Conditions, technical changes reserved. Contents examined and released by TCB, Lepelstraat 1, bus 02.01, B-3290 Lommel, Belgium.

Customer Response Centre: +31 88 999 81 81 or [info@tweha.com](mailto:info@tweha.com).